



TECHNICAL DATA SHEET

DESCRIPTION

The Waterproof Pro Seam Tape™ is the tougher, stronger, and more durable choice for your crawl space encapsulation. Made by one of North America's leading tape manufacturers with our proprietary adhesion requirements, you won't find this tape at any of our competitors....

This product uses our pressure sensitive adhesive formula that achieves 100% strength in 15 minutes at 70 degrees F. How strong is 100% strength? 4.7 pounds of adhesion per square inch! No one can say that about their tape...

Case includes 12 rolls - Save 15% on orders of 12 or more rolls.

PRODUCT APPLICATION

Patching, sealing, bundling and wrapping
Splicing and surface protection
Vapor barrier seaming
Wire hold down
Multi-purpose convention applications
Short term masking for EIFS
Holding poly sheeting barrier film

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Polyethylene (PE) Film
Adhesive	Synthetic Rubber
Adhesion to Steel (oz./in of width) ASTM D-3330	75 (20.5 N/25mm)
Tensile Strength (lbs./in of width) ASTM D-3759	23 (100.7 N/25mm)
Elongation (% at break) ASTM D-3759	75
Total Thickness (mils) ASTM D-3652	7.0 (0.178mm)
Application Temperature Range	+45°F to +120°F (+7°C ~ +49°C)
Operating Temperature Range	+20°F ~ +150°F (-7°C ~ +65°C)
Colors	White

